


Transport Temperature Control System  
**LMK 1.5E**



**DESCRIPTION:** Belt driven unit, for small and medium vehicles and deliveries of fresh perishable foodstuffs (ATP class FNAX)

220V electric stand-by operating version available.

**COMPONENTS:**

- Condensing unit
- Evaporating unit
- Belt driven compressor
- Installation kit
- Digital cab control

**REFRIGERANT:** HFC R-134A  
 Cloro: zero

**REFRIGERATION POWER:** Cooling capacity calculated in accordance with the ATP standards (ambient temperature +30°C):

On the road:	0°C	1791 W
	-10°C	995 W
	-20°C	560 W

Electric stand-by 50Hz:	0°C	980 W
	-10°C	631 W
	-20°C	= W

**DIMENSION (mm):** Condensing unit:

500 x 890 x 220h

Evaporating unit:

530 x 650 x 220h

**WARRANTY:** Available on demand.  
 We guarantee that the unit and all its component are free from defects in materials and workmanship starting from date of installation according to the terms (in months) specified in the warranty

Technical specifications may change without notice.

Manufactured and distributed by:



LAURI s.r.l.  
 Via G. Di Capi, 11/A  
 I-46100 MANTOVA - ITALY  
 Tel. +39 0376 302276  
 Fax +39 0376 302246  
 E mail: info@lauriweb.it  
 URL: www.lauriweb.it