

Transport Temperature Control System
LMK 2.0 PLUS



DESCRIPTION: Belt driven unit for deliveries of fresh perishable foodstuffs on medium vehicles or frozen perishable foodstuffs on small vehicles (ATP class FNAX/FRCX)

220V electric stand-by operating version available.

COMPONENTS:

- Condensing unit
- Evaporating unit
- Belt driven compressor
- Installation kit
- Digital cab control

REFRIGERANT: HFC R-134A - R-404A
 Chlorine: zero

REFRIGERATION POWER: Cooling capacity calculated in accordance with the ATP standards (ambient temperature +30°C):

On road: -1,00°C 1935 W
 -11,05°C 1389 W
 -21,03°C 878 W

Electric stand-by 50Hz: -0,42°C 1068 W
 -10,99°C 943 W
 -17,29°C 556 W

DIMENSION (mm): Condensing Unit:
 500 x 890 x 220h
 Evaporating Unit:
 590 x 790 x 240h

WARRANTY: Available on demand.
 We guarantee that the unit and all its component are free from defects in materials and workmanship starting from date of installation according to the terms (in months) specified in the warranty

Technical specifications may change without notice.

Manufactured and distributed by:



LAURI s.r.l.
 Via G. Di Capi, 11/A - I-46100
 MANTOVA
 Tel. +39 0376 302276
 Fax +39 0376 302246
 E mail: info@lauriweb.it
 URL: www.lauriweb.it