

Transport Temperature Control System  
**LMK 3.5E**



**DESCRIPTION:** Belt driven monoblock unit, for medium insulated van bodies with length from 3,5 m to 5,5 m

400V/3PH/50Hz electric stand-by operating version available.

It can also be equipped with a more powerful compressor to increase its performance

**COMPONENTS:**

- Condensing unit
- Evaporating unit
- Belt driven compressor
- Installation kit
- Digital cab control

**REFRIGERANT:** HFC R-134A - R-404A  
 Chlorine: zero

**REFRIGERATION POWER:** Cooling capacity calculated in accordance with the ATP standards (ambient temperature +30°C):

On the road:	0°C	3160 W
	-10°C	2140 W
	-20°C	1663 W

Electric stand-by 50Hz:	0°C	3265 W
	-10°C	2150 W
	-20°C	1580 W

**DIMENSION (mm):** Condensing unit:  
 550 x 1200 x 400h  
 Evaporating unit:  
 600 x 850 x 300h

**WARRANTY:** Available on demand.  
 We guarantee that the unit and all its component are free from defects in materials and workmanship starting from date of installation according to the terms (in months) specified in the warranty

Technical specifications may change without notice.

Manufactured and distributed by:



LAURI s.r.l.  
 Via G. Di Capi, 11/A - I-46100 MANTOVA  
 Tel. +39 0376 302276  
 Fax +39 0376 302246  
 E mail: info@lauriweb.it  
 URL: www.lauriweb.it